

Safety Salt
Ice Melt

MISC

3007170
Copy - grounds

MATERIAL SAFETY DATA SHEET

Dow Chemical U.S.A. Midland, MI 48674 Emergency Phone: 517-636-4400

MSD: 001452

Page: 1

PRODUCT NAME: CALCIUM CHLORIDE PELLETS 90 (BULK)

Effective Date: 10/16/85 Date Printed: 10/16/85 Product Code: 38051

1. INGREDIENTS:

Calcium chloride	CAS# 010043-52-4	90-92%
Sodium chloride	CAS# 007647-14-5	1- 2%
Potassium chloride	CAS# 007447-40-7	2- 3%
Strontium chloride	CAS# 010476-85-4	1%
Water	CAS# 007732-18-5	BAL.

Substances listed in the Ingredients Section are those identified as being present at a concentration of 1% or greater, or 0.1% if the substance is on the list of potential carcinogens cited in OSHA Hazard Communication Standard. Where proprietary ingredient shows, the identity of this substance may be made available as provided in 29 CFR 1910.1200(I).

2. PHYSICAL DATA:

BOILING POINT: 388F; 198C
VAP PRESS: 0.009 mmHg @ 20C
VAP DENSITY: Not applic.
SOL. IN WATER: Very soluble.
SP. GRAVITY: 2.2
APPEARANCE: White to off white, solid - pellets.
ODOR: Odorless.

3. FIRE AND EXPLOSION HAZARD DATA:

FLASH POINT: Not applicable.
METHOD USED: Not applicable.

FLAMMABLE LIMITS
LFL: Not applicable.
UFL: Not applicable.

EXTINGUISHING MEDIA: Non-combustible.

(Continued on Page 2)

(R) Indicates a trademark of The Dow Chemical Company

MATERIAL SAFETY DATA SHEET

Dow Chemical U.S.A. Midland, MI 48674 Emergency Phone: 517-636-4400

MSD: 001452 Page: 2

PRODUCT NAME: CALCIUM CHLORIDE PELLETS 90 (BULK)

Effective Date: 10/16/85 Date Printed: 10/16/85 Product Code: 38051

3. FIRE AND EXPLOSION HAZARD DATA: (CONTINUED)

FIRE & EXPLOSION HAZARDS: None.

FIRE-FIGHTING EQUIPMENT: Wear positive pressure self-contained breathing apparatus.

4. REACTIVITY DATA:

STABILITY: (CONDITIONS TO AVOID) Decomposes >350F.

INCOMPATIBILITY: (SPECIFIC MATERIALS TO AVOID) Metals will slowly corrode in aqueous calcium chloride solutions. Aluminum (and its alloys) and yellow brass will be attacked by calcium chloride. Product attracts moisture and gives off heat while dissolving.

HAZARDOUS DECOMPOSITION PRODUCTS: Not applicable.

HAZARDOUS POLYMERIZATION: Will not occur.

5. ENVIRONMENTAL AND DISPOSAL INFORMATION:

ACTION TO TAKE FOR SPILLS/LEAKS: No special precautions necessary - sweep up and return to container or discard. Walking surfaces may remain wet longer due to moisture being held by spilled materials.

DISPOSAL METHOD: Wash away with large excess of water or bury. Keep out of drinking water sources. Comply with local, state, and federal regulations.

6. HEALTH HAZARD DATA:

EYE: May cause moderate to severe eye irritation with corneal injury, which may be slow to heal.

SKIN CONTACT: Short single exposure not likely to cause

(Continued on Page 3)

(R) Indicates a trademark of The Dow Chemical Company

MATERIAL SAFETY DATA SHEET

Dow Chemical U.S.A. Midland, MI 48674 Emergency Phone: 517-636-4400

MSD: 001452 Page: 3

PRODUCT NAME: CALCIUM CHLORIDE PELLETS 90 (BULK)

Effective Date: 10/16/85 Date Printed: 10/16/85 Product Code: 38051

6. HEALTH HAZARD DATA: (CONTINUED)

significant skin irritation. Prolonged or repeated exposure may cause skin irritation, even a burn. May cause more severe response if skin is damp and/or abraded, or if material is confined to skin.

SKIN ABSORPTION: A single prolonged exposure is not likely to result in the material being absorbed through skin in harmful amounts. The LD50 for skin absorption in rabbits is >5000 mg/kg.

INGESTION: Single dose oral toxicity is low. The oral LD50 for rats is 1090-1668 mg/kg. Ingestion may cause gastrointestinal irritation or ulceration.

INHALATION: Vapors are unlikely due to physical properties. Dust may cause irritation to upper respiratory tract.

SYSTEMIC & OTHER EFFECTS: Results of in vitro mutagenicity tests have been negative for CaCl₂.

7. FIRST AID:

EYES: Irrigate with flowing water immediately and continuously for 15 minutes. Consult medical personnel.

SKIN: Wash off in flowing water or shower.

INGESTION: If swallowed, induce vomiting immediately by giving two glasses of water and sticking finger down throat. Call a physician. (Never give anything by mouth or attempt to induce vomiting in an unconscious person.)

INHALATION: Remove to fresh air if effects occur. Consult a physician.

NOTE TO PHYSICIAN: If burn is present, treat as any thermal burn, after decontamination. No specific antidote. Supportive care. Treatment based on judgment of the physician in response to reactions of the patient.

MATERIAL SAFETY DATA SHEET

Dow Chemical U.S.A. Midland, MI 48674 Emergency Phone: 517-636-4400

MSD: 001452

Page: 4

PRODUCT NAME: CALCIUM CHLORIDE PELLETS 90 (BULK)

Effective Date: 10/16/85 Date Printed: 10/16/85 Product Code: 38051

8. HANDLING PRECAUTIONS:

EXPOSURE GUIDELINE(S): Dow IHG is 10 mg/m³ for calcium chloride, sodium chloride and potassium chloride.

VENTILATION: Provide general and/or local exhaust ventilation to control airborne levels below the exposure guidelines.

RESPIRATORY PROTECTION: Atmospheric levels should be maintained below the exposure guideline. When respiratory protection is required for certain operations, use an approved air-purifying respirator. In dusty atmospheres, use an approved dust respirator.

SKIN PROTECTION: For brief contact, no precautions other than clean body-covering clothing should be needed. Use protective clothing impervious to this material. Selection of specific items such as gloves, boots, apron, or full-body suit will depend on operation. If skin comes in contact with contaminated clothing, remove this clothing immediately, wash skin area with soap and water, and launder clothing before reuse.

EYE PROTECTION: Safety glasses should be sufficient for most operations; however, for dusty operations or when handling solutions of the material, wear chemical goggles. Eye wash fountain should be located in immediate work area.

9. ADDITIONAL INFORMATION:

SPECIAL PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Avoid eye and prolonged skin contact. Always use cool water (temperature less than 80F, 27C) when dissolving calcium chloride. Heat developed by solutions is very high during dissolving and mixing. When exposed to the atmosphere, calcium chloride will pick up water and form a solution. Leather clothing and shoes will be damaged by calcium chloride.

MSDS STATUS: Revised 2, 3, 4, 6, 7, and 8.

(Continued on Page 5)

(R) Indicates a trademark of The Dow Chemical Company

M A T E R I A L S A F E T Y D A T A S H E E T

Dow Chemical U.S.A. Midland, MI 48674 Emergency Phone: 517-636-4400

MSD: 001452 Page: 5

PRODUCT NAME: CALCIUM CHLORIDE PELLETS 90 (BULK)

Effective Date: 10/16/85 Date Printed: 10/16/85 Product Code: 38051

(R) Indicates a trademark of The Dow Chemical Company
The Information Herein Is Given In Good Faith, But No Warranty,
Expressed Or Implied, Is Made. Consult The Dow Chemical Company
For Further Information.